

SECTION 1 - MANUFACTURER INFORMATION

MANUF/DIST : CHEM-POWER MFG DIV/ FOSTER & CO., INC
15 Wing Drive EMERGENCY PHONE.....: 973-267-4100
Cedar Knolls PREPARATION/REVISION DATE: 02/14/02
NJ 07927
PREPARER/CONTACT: Gary Adam, Chemist
LOCATION : Whs 1

TRADE NAME/SYNONYMS...: REGAL PLP
CHEMICAL NAME/SYNONYMS: Moly Lube
CHEMICAL FAMILY.....: Petroleum Hydrocarbon Grease
FORMULA.....: Complex Mixture
PRODUCT CODE.....: 12-04

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

* * * * *
* HEALTH..... 1 *
* FLAMMABILITY.. 0 *
* REACTIVITY.... 0 *
* PROTECTION.... 0 *
* * * * *

SECTION 2 - HAZARDOUS INGREDIENTS

THIS PRODUCT CONTAINS HAZARDOUS INGREDIENTS : YES

CHEMICAL/COMMON NAME	CAS-NUMBER	%	PEL-OSHA TLV-ACGIH
Organo Lead	61790-14-5	N/I	N/I

*There is an action level above which exposed employees blood must be monitored for Lead content. The action level is .03mg/m3. The maximum allowed in blood is .04mg/100gm. See 29 CFR 1910.1025.

THIS PRODUCT CONTAINS CARCINOGENS (NTP, IARC, or OSHA):NO

CHEMICAL/COMMON NAME	CAS-NUMBER	%	NTP	IARC	OSHA
N/A	N/A	N/A	N/A	N/A	N/A

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute And Chronic)-
May be absorbed through skin. May cause eye and skin irritation with prolonged contact.

PRIMARY ROUTES OF ENTRY-
Skin and eyes.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-
None known.

EMERGENCY FIRST AID PROCEDURES-

EYES: Immediately flush with water for 15 Minutes. Hold eyes open to rinse entire area. Call physician.

INGESTION: If conscious, induce vomiting, call physician or poison control center immediately.

SKIN: Wash thoroughly with soap and water.

SECTION 4 - CHEMICAL DATA

.....

BOILING POINT (F).....: N/A	SPECIFIC GRAVITY (WATER=1).....: 0.951
VAPOR PRESSURE (mmHg): N/A	PERCENT VOLATILE BY VOLUME (%): N/A
VAPOR DENSITY (AIR=1): N/A	EVAPORATION RATE (N/A =1): N/A

SOLUBILITY IN WATER-
Negligible.

APPEARANCE AND ODOR INFORMATION-
Black semi-solid with mineral oil odor.

SECTION 5 - PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 356+, COC FLAMMABLE LIMITS : Lel=N/A UEL=N/A

EXTINGUISHING MEDIA-

Dry chemical, carbon dioxide, foam, sand or earth, waterfog.

SPECIAL FIRE FIGHTING PROCEDURES-

Self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS-

Dense smoke.

INCOMPATIBILITY (Materials To Avoid)-

N/I

HAZARDOUS DECOMPOSITION PRODUCTS-

N/I

WILL HAZARDOUS POLYMERIZATION OCCUR-

No.

CONDITIONS TO AVOID FOR POLYMERIZATION-

None known.

IS THE PRODUCT STABLE-

Yes.

08-09-02
CSS-14038

MATERIAL SAFETY DATA SHEET 00142
CHEM-POWER DIV/FOSTER & CO

PAGE 4

ADDITIONAL COMMENTS-

Shipping Name: Grease Lubricant, NOI. Class 65.