

SECTION 1 - MANUFACTURER INFORMATION
.....

MANUF/DIST : CYBERBOND L.L.C./ FOSTER AND COMPANY, DISTRIBUTOR
401 North Raddant Rd EMERGENCY PHONE.....: 630-761-8900
PREPARATION/REVISION DATE: 02/14/02
Batavia, Illinois 60510
PREPARER/CONTACT: Lawrence Serkanic 24 hr 800-424-9300
LOCATION : Whs 1

TRADE NAME/SYNONYMS...: TITAN 7567
CHEMICAL NAME/SYNONYMS: Anerobic Adhesive
CHEMICAL FAMILY.....: Cyanoacrylate Adhesives
FORMULA.....: Mixture of Cyanoacrylates
PRODUCT CODE.....: 514-204 Z

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

* * * * *
* HEALTH..... 1 *
* FLAMMABILITY.. 1 *
* REACTIVITY.... 1 *
* PROTECTION.... C *
* * * * *

SECTION 2 - HAZARDOUS INGREDIENTS

THIS PRODUCT CONTAINS HAZARDOUS INGREDIENTS : YES

| CHEMICAL/COMMON NAME | CAS-NUMBER | % | PEL-OSHA | TLV-ACGIH |
|----------------------|------------|---|----------|-----------|
| Cumene Hydroperoxide | 80-15-9 | 2 | N/I | N/I |

THIS PRODUCT CONTAINS CARCINOGENS (NTP, IARC, or OSHA):NO

| CHEMICAL/COMMON NAME | CAS-NUMBER | % | NTP | IARC | OSHA |
|----------------------|------------|-----|-----|------|------|
| None listed. | N/A | N/A | N/A | N/A | N/A |

SECTION 3 - HEALTH HAZARD DATA
.....

HEALTH EFFECTS (Acute And Chronic)-
CHRONIC: None expected. No target organ effects known or exposure limit estab.
ACUTE: SKIN AND EYE CONTACT: Warning! Irritating, may bond skin rapidly and strongly. May also bond eyelid to eyelid and/or eye. A large drop may cause a burn upon solidification.
INHALATION: Caution! Vapors may cause irritation of bronchial passages. Avoid prolonged inhalation.
ORAL INGESTION: It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres to the mouth. The lips may be stuck together. LD50 unknown.
CAUTION: Contact with cotton or wool can cause a strong exothermic reaction

which can cause burns or fire.

PRIMARY ROUTES OF ENTRY-
Skin contact, eye contact, inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-
None known.

EMERGENCY FIRST AID PROCEDURES-
SKIN: Immerse bonded skin in warm, soapy water. Do not force separation.
EYES: Flush thoroughly with lukewarm or tepid water for at least 15 minutes.
Call physician immediately.
INHALATION: Move to fresh air. If irritation persists consult physician. It is unlikely that the small containers provided could supply enough material to cause an inhalation injury.
INGESTION: Mouth saliva should lift the adhesive in 12 to 48 hours. Do not force removal. Do not swallow adhesive when it loosens.

SECTION 4 - CHEMICAL DATA

.....

| | |
|-------------------------------|---|
| BOILING POINT (F).....: >300F | SPECIFIC GRAVITY (WATER=1).....: 1.25 |
| VAPOR PRESSURE (mmHg): v.low | PERCENT VOLATILE BY VOLUME (%)......: 0 |
| VAPOR DENSITY (AIR=1): N/I | EVAPORATION RATE (N/I =1): N/I |

SOLUBILITY IN WATER-
Negligible

APPEARANCE AND ODOR INFORMATION-
Colorless liquid with slightly pungent odor.

SECTION 5 - PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 200F SCC FLAMMABLE LIMITS : Lel=N/I UEL=N/I

EXTINGUISHING MEDIA-
Water, CO2, Foam or Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES-
Wear full protective equipment including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS-
CAUTION!! Contact with cotton or wool may result in a strongly exothermic reaction which can cause burns or a fire. Material can float on water and cause fire to spread.

INCOMPATIBILITY (Materials To Avoid)-
Bases, wool and cotton.

HAZARDOUS DECOMPOSITION PRODUCTS-
Irritating gases are released during combustion.

07-30-02
CSS-14038

MATERIAL SAFETY DATA SHEET 00382
CHEM-POWER DIV/FOSTER & CO

PAGE 4

MAINTENANCE PRECAUTIONS-
N/A

OTHER PRECAUTIONS-
Keep out of reach of children!

ADDITIONAL COMMENTS-
Unregulated by DOT.